

Maintenance ladder

The free-standing solution for working at great heights of up to 12 m, safe-standing, simple height adjustment and castors for mobility.

Product description

- Height of top ladder can be adjusted with a rope.
- Locks securely thanks to automatic spring loaded pawls.
- 400 x 400 mm platform made of embossed aluminium plate.
- Guides with plastic runners.
- Stable back hoop and spacious tool tray.
- Two stabiliser bars supplied as standard, with polyamide swivel castors (150 mm diameter) and height adjusters (adjustment range 150 mm).
- Ladder and support section connected by two longitudinal braces.
- Stiles made from tubular box sections.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 265 mm
 Tread depth: 30 mm
 Type rung/tread: serrated
 Width: 2 m

Hints and special features

Safe standing at great heights of up to 12 m with maximum mobility.

Product variants

Order number	Length	Overall length, extended	Overall length, retracted	Platform height	Transport dimensions	Weight	Working height
41342	2.4 m	7.5 m	4.55 m	6.2 m	4.730 mm × 690 mm × 300 mm	68 kg	8.2 m
41343	2.95 m	9.45 m	5.65 m	8.1 m	5.900 mm × 720 mm × 300 mm	86 kg	10.1 m
41346	3.55 m	11.4 m	6.7 m	10 m	7.000 mm × 600 mm × 330 mm	144 kg	12 m