


Platform steps

Compact work platform with easy-going steps. Choice of stationary or mobile version (for moving quickly to another working position). Ideal for work over long periods, even with tools.

Product description

- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Chassis available in a non-static version as an option.
- Configurable up to a vertical height of 1,500 mm (from 1,000 mm with horizontal stabiliser bar for safe standing).
- Assembly elements: Support section assembly elements selectable without wheel or as a stationary work platform with floor brackets.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

Product variants

Order number	Inclination	Number of treads	Overall span	Tread width	Vertical height
40855520	45 °	2	951 mm	600 mm	400 mm
40855521	45 °	3	1151 mm	600 mm	600 mm
40855522	45 °	4	1351 mm	600 mm	800 mm
40855523	45 °	5	1541 mm	600 mm	990 mm
40855524	45 °	2	951 mm	800 mm	400 mm
40855525	45 °	3	1151 mm	800 mm	600 mm
40855526	45 °	4	1351 mm	800 mm	800 mm
40855527	45 °	5	1541 mm	800 mm	990 mm
40855528	45 °	2	951 mm	1000 mm	400 mm
40855529	45 °	3	1151 mm	1000 mm	600 mm



Order number	Inclination	Number of treads	Overall span	Tread width	Vertical height
40855530	45 °	4	1351 mm	1000 mm	800 mm
40855531	45 °	5	1541 mm	1000 mm	990 mm
40855540	60 °	2	864 mm	600 mm	500 mm
40855541	60 °	3	1008 mm	600 mm	750 mm
40855542	60 °	4	1147 mm	600 mm	990 mm
40855544	60 °	2	864 mm	800 mm	500 mm
40855545	60 °	3	1008 mm	800 mm	750 mm
40855546	60 °	4	1147 mm	800 mm	990 mm
40855548	60 °	2	864 mm	1000 mm	500 mm
40855549	60 °	3	1008 mm	1000 mm	750 mm
40855550	60 °	4	1147 mm	1000 mm	990 mm